

UN 38.3 Test Summary Report

Lithium Cell or Battery Test Summary in Accordance with Section 2.9.4 UN Model Regulations and Sub-section 38.3 of the UN Manual of Tests and Criteria, Part III, subsection 38.3.5

<p>[a] <input type="checkbox"/> Cell <input checked="" type="checkbox"/> Battery <input type="checkbox"/> Product <input checked="" type="checkbox"/> Tested Type Part #: TLM-1530/HP <input type="checkbox"/> Same Type Part #:</p>	<p>[d] Unique report ID: 15Q-810</p>
<p>[b] Manufacturer Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com</p>	<p>[e] Report date: 2007.10.01</p>
<p>[b] Manufacturer Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com</p>	<p>[c] Test Laboratory Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com</p>

Same Type Part Numbers # (all): Standard: 12 0 12531 02, Tags: 12 0 12532 02,
Polarised tags: 12 0 12537 02, all other configurations with harness and cable of this cell with part number:
12 0 1253x xx.


[f] (i) Li-ion Li-metal.

(iv) **Description:** Primary (non-rechargeable) 4 V Lithium battery, assembled from 1 (one) "2/3AA" sized TLM-1530/HP cell. The TLM-1530/HP battery may come with optional suffixes consisting of a "/" followed by one or more letters and a digit. These suffixes indicate different types of finishing to the battery e.g. tags or harness. Tadiran manufactures all cells/batteries under a quality management system as required under this regulation.


(ii) Mass: 11 g
(iii) Watt hour rating or Lithium content: 0.08 g
(v) Cell Battery Product. Model number/Part number: TLM-1530/HP

[g] List of Tests Conducted	Result (Pass / Fail / N.A.)	Test record reference
38.3.4.1 T.1: Altitude simulation	Pass	Page 5
38.3.4.2 T.2: Thermal test	Pass	Page 6
38.3.4.3 T.3: Vibration	Pass	Page 7
38.3.4.4 T.4: Shock	Pass	Page 8
38.3.4.5 T.5: External short circuit	Pass	Page 9
38.3.4.6 T.6: Impact/Crush (cell only test)	Pass	Page 10 & 11
38.3.4.7 T.7: Overcharge (N.A for Li-metal only)	N.A.	
38.3.4.8 T.8: Forced discharge (cell only test)	Pass	Page 4

[h] Battery assembly: Not Applicable. UN38.3.3 (f) UN38.3.3 (g)
[i] Test Reference: UN Manual of Tests and Criteria, Part III, sub-section 38.3. *Fourth revised edition*

[j] Signatory A. Date: 2018.02.12
Name: Marc Henn
Title: Application Engineering Manager
Signature:




[j] Signatory B. Date: 2018.02.12
Name: Olaf G. Lichtlein
Title: General Manager
Signature:


Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Tadiran and, should Tadiran consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.