

UN 38.3 Test Summary Report

Lithium Cell or Battery Test Summary in Accordance with Section 2.9.4 LIN Model Regulations and Sub-section 38.3 of the LIN Manual of Tests and Criteria Part III. subsection 38.3.5

| [a] ⊠ Cell □ Battery □ Product |
|---------------------------------|
| ☑ Tested Type Part #: HLC-1530A |
| ☐ Same Type Part #: |
| [b] Manufacturer |
| Tadiran Batteries Ltd. |
| 44 Yitzhak Rabin Blvd, |
| Kiryat Ekron, |
| Israel 7695001 |
| T. +972 8 9 44 503 |
| sales@tadiran-batt.com |
| www.tadiran.com |

| [d] Unique report ID: 15Q-654 | |
|-------------------------------|--|
| [e] Report date: August 2014 | |
| [c] Test Laboratory | |
| Tadiran Batteries Ltd. | |
| 44 Yitzhak Rabin Blvd, | |
| Kiryat Ekron, | |
| Israel 7695001 | |
| T. +972 8 9 44 560 | |
| aya-d@tadiran-batt.com | |
| www.tadiran.com | |

[f] (i) \boxtimes Li-ion \boxtimes Li-metal.

(iv) <u>Description:</u> HLC-1530A is designed to be connected in parallel to a primary lithium metal battery with OCV of up to 3. 9V, consists of a single cell and can be transported as a lithium metal battery under UN numbers 3090 and 3091. The HLC-1530A battery may come with the suffixes consist of a "/" followed by one or two letters and digits which indicate different finishing such as /T, /TP, /PT2, etc.

Tadiran manufactures all cells/batteries under a quality management system as required under this regulation.

(ii) Mass: 12 g

(iii) ⊠ Watt hour rating or ⊠ Lithium content: 0.43 Wh and 0g

(v) ⊠ Cell □ Battery □ Product. Model number/Part number: HLC-1530A

| [g] List of Tests Conducted | Result (Pass / Fail / N.A.) | Test record reference |
|--|-----------------------------------|-----------------------|
| 38.3.4.1 T.1: Altitude simulation | Pass | 15Q-654 |
| 38.3.4.2 T.2: Thermal test | Pass | 15Q-654 |
| 38.3.4.3 T.3: Vibration | Pass | 15Q-654 |
| 38.3.4.4 T.4: Shock | Pass | 15Q-654 |
| 38.3.4.5 T.5: External short circuit | Pass | 15Q-654 |
| 38.3.4.6 T.6: Impact/Crush (cell only test) | Pass | 15Q-654, 15Q-960 |
| 38.3.4.7 T.7: Overcharge (N.A for Li-metal only) | N.A. | N.A. |
| 38.3.4.8 T.8: Forced discharge (cell only test) | Pass | 15Q-654 |
| [h] Battery assembly: ☐ Not Applicable. ☒ UN38.3 | 3.3 (f) UN38.3.3 (g) | |
| [i] Test Reference: UN Manual of Tests and Criteria, | Part III, sub-section 38.3. Sixth | revised edition |

| [j] Signatory A. Date: 2020.01.27 |
|-----------------------------------|
| Name: Aya Daniel |
| Title: Quality Manager |
| Signature. |
| 1 |
| 1 Daniel |



[j] Signatory B. Date: 2020.01.27

Name: Kobi Pinsky

Title: VP Marketing and Sales

Signature.

Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Tadiran and, should Tadiran consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.