

UN 38.3 Test Summary Report

Lithium Cell or Battery Test Summary in Accordance with Section 2.9.4 UN Model Regulations and Sub-section 38.3 of the UN Manual of Tests and Criteria, Part III, subsection 38.3.5

| |
|--|
| [a] <input checked="" type="checkbox"/> Cell <input type="checkbox"/> Battery <input type="checkbox"/> Product <input checked="" type="checkbox"/> Tested Type Part #: SL-2880 <input checked="" type="checkbox"/> Same Type Part #: TL-4940 |
| [b] Manufacturer Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com |


| |
|--|
| [d] Unique report ID: 15Q-610 |
| [e] Report date: 2003.09.01 |
| [c] Test Laboratory Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com |

Same Type Part Numbers # (all): All configurations with harness and cable of this battery with part number: 11 21880x xx


| |
|--|
| [f] (i) <input type="checkbox"/> Li-ion <input checked="" type="checkbox"/> Li-metal. (iv) Description: Primary (non-rechargeable) 3.7 V Lithium Thionyl Chloride (Li-SOCl ₂) battery, assembled from 1 (one) "D" sized TL-4940 cell. The TL-4940 cell may come with optional suffixes consisting of a "/" followed by one or more letters and a digit. These suffixes indicate different types of finishing to the cell. Tadiran manufactures all cells/batteries under a quality management system as required under this regulation. (ii) Mass: 93 g (iii) <input type="checkbox"/> Watt hour rating or <input checked="" type="checkbox"/> Lithium content: 5 g (v) <input checked="" type="checkbox"/> Cell <input type="checkbox"/> Battery <input type="checkbox"/> Product. Model number/Part number: TL-4940 |
|--|

| [g] List of Tests Conducted | Result (Pass / Fail / N.A.) | Test record reference |
|--|-----------------------------|-----------------------|
| 38.3.4.1 T.1: Altitude simulation | Pass | Page 5 |
| 38.3.4.2 T.2: Thermal test | Pass | Page 6 |
| 38.3.4.3 T.3: Vibration | Pass | Page 7 |
| 38.3.4.4 T.4: Shock | Pass | Page 8 |
| 38.3.4.5 T.5: External short circuit | Pass | Page 9 |
| 38.3.4.6 T.6: Impact/Crush (cell only test) | Pass | Page 10 |
| 38.3.4.7 T.7: Overcharge (N.A for Li-metal only) | N.A. | N.A. |
| 38.3.4.8 T.8: Forced discharge (cell only test) | Pass | Page 11 |

[h] Battery assembly: Not Applicable. UN38.3.3 (f) UN38.3.3 (g)
 [i] Test Reference: UN Manual of Tests and Criteria, Part III, sub-section 38.3. *fourth revised edition*

| |
|---|
| [j] Signatory A. Date: 2018.02.12 Name: Marc Henn Title: Application Engineering Manager Signature:  |
|---|



| |
|--|
| [j] Signatory B. Date: 2018.02.12 Name: Olaf G. Lichtlein Title: General Manager Signature:  |
|--|

Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Tadiran and, should Tadiran consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.